



Electrical and Control

ET7054

Voltage	220-240V
Power	10W
Power Supply	Built In
Control	ON/OFF
Insulation Class	Class I
Cable	0.5M H05RN-F 3x1mm ²
Environmental	-20 °C ~ 50 °C




LED and Optics

LED Brand	Citizen / CREE
LED Quantity	COB X 1
Beam Angle	15°/24°/36°/50°
Delivered Lumen	911lm(24° 3000K)
Colour Rendering	CRI 80
SDCM	≤3
CCT	3000K/4000K/5000K
LED Optic	PMMA

Physical

Housing	Aluminum
Lens Material	Glass
External Screw	Stainless steel material
Surface Treatment	Anticorrosive coating
Net Weight	1.2KG
Warranty	3 years
Rating	IP65
Impact Protection	IK08

Certifications



RAL9011

RAL9006


RAL9016

Mineral bronze


RAL7012

RAL7016


Photometric curves:




H(m)	ø(m)	lx(MAX)
2	0.68	1275
4	1.37	319
6	2.06	141
8	2.74	79



H(m)	ø(m)	lx(MAX)
2	1.14	751
4	2.29	188
6	3.43	83
8	4.58	47



H(m)	ø(m)	lx(MAX)
2	1.57	450
4	3.14	112
6	4.71	50
8	6.28	28



H(m)	ø(m)	lx(MAX)
2	1.83	273
4	3.67	68
6	5.50	30
8	7.34	17


Accessory



Back light

ET296

Anti glare Visor



ET373

Honeycomb

