

Electrical and Control

ET7076

Voltage	220-240V
Power	28W
Power Supply	Built-in
Control	ON/OFF
Insulation Class	Class I
Cable	0.5M H05RN-F 3x1mm ²
Environmental	-20 °C ~ 50 °C

LED and Optics

LED Brand	Citizen / CREE
LED Quantity	COB X 1
Beam Angle	15°/24°/36°/50°
Delivered Lumen	2547lm(24° 3000K)
Colour Rendering	CRI 80
SDCM	≤3
CCT	3000K/4000K/5000K
LED Optic	PMMA


Physical

Housing	Aluminum
Lens Material	Glass
External Screw	Stainless steel material
Surface Treatment	Anticorrosive coating
Net Weight	3.6KG
Warranty	3 years
Rating	IP65
Impact Protection	IK08


Certifications




Photometric curves:




H(m)	ø(m)	lx(MAX)
2	0.68	4299
4	1.36	1075
6	2.04	478
8	2.72	269




H(m)	ø(m)	lx(MAX)
2	0.87	3282
4	1.73	820
6	2.60	365
8	3.47	205



H(m)	ø(m)	lx(MAX)
2	1.32	1615
4	2.64	404
6	3.96	179
8	5.28	101



H(m)	ø(m)	lx(MAX)
2	1.82	890
4	3.65	222
6	5.47	99
8	7.29	55



H(m)	ø(m)	lx(MAX)
2	0.66	1423
4	1.33	355
6	1.99	158
8	2.66	89

